

POPPET TYPE PILOT OPERATED SOLENOID VALVES



5/2 Pilot Operated Solenoid Valves


Features:

- Bubble tight shut off.
- Mounts in any position.
- Suitable for high speed cycling.
- Speed upto 600 cycle / min.
- Life > 10 million cycles.
- Good Flow Characterstics



Technical Specifications:

Model	K-51404			
Medium	Filtered, Lubricated, Compressed air			
Port Size	G 3/8 BSP (F)			
Orifice	10			
Operating presure (Bar)	2 -10			
Flow Rate	1100			
Electrical				
Power Consuption	AC		DC	
Voltage Range	24	230	12	24
Power Consuption (W)	6 8		3	
Duty Cycle	Continues			
Type Of Coil Protection	IP67			
Class of Insulation	Class F			
Material of Construction	Aluminium , Brass , Stainless , Nitrile			




CAUTION:-

- A. To ensure proper functioning.
- 1. Please ensure that inlet port is connected to compressor air source.
- 2. Exhuast should not be restricted.
- B. AC coil valve should not be used on DC coil valve and vice versa.

APPLICATION: -

Double acting cylinder, Centrifuge, Air drier, Air motor, Water treatment, Material Handling, Foundry, Gas plant etc.



Manufactured by:

Kushako India

Office: 490, Narayan Peth, Opp. Pune Marathi Granthalaya, Pune - 411030. (Maharashtra), Website: www.kushakoindia.com Works: Sr.No. 25/1A, Village Nanded, Sinhgad Road, Tal - Haveli, Dist. Pune -411041

Tel. No: 901169077 / 7620674777

E-mail: kushako.india@gmail.com/kushakoindia1992@gmail.com